

衛生蝶閥

應用:

- 設計,製造符合IDF&3A衛生標準
- 閥體&蝶板精密鑄造
- 可選用對焊, 卡箍及螺紋連接端
- 蝶板衛生鏡面拋光
- 鑄件通過TUV AD 2000-Merkblatt W0認證

標準:

- 設計: ISO 2852, MIL-C-27487, DIN 11851, DIN 405
- 檢驗&測試: EN 12266, API 598

規格說明:


- 工作壓力: 10 Bar at 38° C (100° F)
- 工作溫度: -29° C to 120° C (-20° F to 248° F)

材料

閥體	CF8M/SCS14, CF3M/SCS16	閥座	Silicone, EPDM
蝶板	CF3M/SCS16	手柄	CF8/SCS13



KB-02C




KB-021, 對焊

單位: mm

尺寸	d	D	L	H	W	N
1"	23.0	74	65	95	142	19
1-1/2"	35.7	87	75	101	142	19
2"	47.8	98	75	113	147	19
2-1/2"	59.5	112	85	115	147	19
3"	72.9	131	90	125	155	19
4"	97.6	156	105	137	155	19



KB-021




KB-02C, 卡箍

單位: mm

尺寸	d	D	L	H	W	N
1"	23.0	74	84	95	142	19
1-1/2"	35.7	87	84	101	142	19
2"	47.8	98	84	113	147	19
2-1/2"	59.5	112	100	115	147	19
3"	72.9	132	110	125	155	19
4"	97.6	156	120	137	155	19



KB-Q2C




KB-020, 外螺紋

單位: mm

尺寸	d	D	L	H	W	N
1"	23.0	84	80	101	142	19
1-1/2"	35.7	98	80	106	142	19
2"	47.8	109	85	110	147	19
2-1/2"	59.5	129	90	123	147	19
3"	72.9	148	100	133	155	19
4"	97.6	168	100	143	155	19

KB-Q2C



KB-Q2C 快速接頭

單位: mm

尺寸	d	D	L	H	W	N
1"	23.0	74	119	95	142	19
1-1/2"	35.7	87	155	101	142	19
2"	47.8	98	159	113	147	19
2-1/2"	59.5	112	167	115	147	19
3"	72.9	132	182	125	155	19
4"	97.6	156	187	137	155	19